

FALL ARREST & RESCUE

V-SHOCK® NON-LEADING EDGE PERSONAL FALL LIMITER

- V-Shock® Web PFLs feature easy-to-understand housing colour, dashboard labels, and iconography to help make PPE selection on the jobsite quick and easy
- Grey housing identifies the PFL as being for Overhead use vs. Leading Edge, and includes an icon signifying "Non Leading Edge"
- Easy-to-understand clearance charts have been added to the label pack, making it easier to access clearance data without the manual
- Lifeline Length: 6'
- Lifeline Material: Web
- Swivel or Stationary: Swivel
- Unit Connector: Carabiner
- Unit Connector Material: Steel
- Lifeline Connector: Snap Hook
- Lifeline Connector Material: Aluminum
- CSA Certification: SRL



Model No.	Mfg. No.	No. of SRLs	Snap Hook Type	Price /Each
SHC065	VSOHW-011-NC-C	1	ALTAKS-C	
SHC067	VSOHW-011-NH-C	1	AL36CLS-C	
SHC071	VSOHW-012-QC-C	2	ALTAKS-C	
SHC073	VSOHW-012-QH-C	2	AL36CLS-C	

LAD-SAF™ CABLE VERTICAL SAFETY SYSTEM

- Designed to meet the requirements of the new ANSI Z359.16 standard, along with OSHA 1910.140 and 1926.502, when used with our Lad-Saf X3 Detachable Cable Sleeve (6160054) and Lad-Saf X2 Detachable Cable Sleeve (6160030)
- Reengineered to simplify and speed up the installation process
- Integrated fall arrest-rated anchor point on top bracket rated to 3600 lbs provides 100% tie-off capability
- Galvanized steel bracket fits up to 1-1/8" (2.85 cm) rung diameter and attaches to two rungs
- Integrated tension-indicating bottom bracket takes the guesswork out of installation
- Compatible with Lad-Saf™ X3 Detachable Cable Sleeve for better climbing performance and fall protection (sold separately)
- Non-metallic Cable Guide hardware for easy-to-use hand operation, with mounting hardware for systems up to 199' (60.6 m), fits up to 1-1/8" (2.85 cm) rung diameter (recommended one every 25' / 7.6 m)
- Material: Galvanized Steel
- Installation Type: Permanent
- Maximum No. of Users: 2
- Single Point Anchor Rating: 3600 lbs.
- Weight Capacity (2 Users): 620 lbs. (281 kg)
- Weight Capacity (1 User): 310 lbs. (140 kg)
- Specification(s) Met: ANSI Z359.16, OSHA 1910.29, OSHA 1926.1053, RR-W-410
- Diameter: 3/8"



Model No.	Mfg. No.	Length'	Price /Each
SGY439	6118020	20	
SGY440	6118030	30	
SGP408	6160054	Lad-Saf™ X3 Detachable Cable Sleeve	

ROLLGLISS™ R550 RESCUE & DESCENT DEVICE

- Emergency rescue and evacuation from a wide variety of elevated work areas
- Fully automatic controlled descent
- Bidirectional design enables multiple rescues
- Built-in rescue lifting wheel
- 100 ft. (30.5 m) 3/8" (9.5 mm) kernmantle rope lifeline
- Rated for up to 1 640 ft. (500 m) height for one user, 575 ft. (175 m) for two users
- Compact and lightweight design
- High strength corrosion resistant construction
- Integrated rope ears
- Dual brake design
- Equipped with i-Safe™
- Kit also contains 4 ft. (1.2 m) anchor sling, two carabiners and carrying bag
- No. of users: 2
- Lifeline material: Kernmantle
- Harness connection: Carabiner
- Anchorage connection type: Snap hook
- CSA Standard Z259.2.2



Model No. **SDL610**
Mfg. No. 3327100
Price/Each \$

PULLEY - ROLLGLISS™ R550

- Single
- 9-16 mm

Model No. **SDL611**
Mfg. No. 9504733
Price/Each \$



ROOF ANCHORS

- Fast and easy installation
- Installs to sloped or flat wood and metal decking roofs
- Non-penetrating design
- Swiveling self-retracting lifeline bracket
- Compact and lightweight design
- Secondary D-ring anchor point
- Adjustable legs, 360-degree swiveling
- Pair the DBI-SALA® roof anchors with the 3M™ DBI-SALA® Smart Lock SRLs



Model No.	Mfg. No.	Description	Price /Each
SGJ694	2190073	3M™ DBI-SALA® Standing Seam Roof Anchor	
SGJ695	2190071	3M™ DBI-SALA® Swiveling Roof Anchor	
SGJ696	2190074	3M™ DBI-SALA® Construction Roof Anchor	
SGJ697	2190072	3M™ Protecta® Standing Seam Roof Anchor	
SGJ698	2190070	3M™ Protecta® Swiveling Roof Anchor	