

## CROSS-ARM STRAPS

- Web cross-arm strap wraps around I-beams and other structures
- Attaches with a 2" D-ring that slips through a 3" D-ring
- Forms a secure attachment point for lanyards and other connecting devices
- 400-lb. maximum capacity

**Honeywell**  
**MILLER**

Model No.	Mfg. No.	Length'	Price /Each
SEP327	8183/2FTGN	2	
SEP329	8183/4FTGN	4	
SD009	8183/6FTGN	6	
SEP316	8183/10FTGN	10	



## ANCHORAGE CONNECTOR WITH HARDWARE

- Designed as the intermediary for securing a connecting device to an anchorage
- Meets OSHA 1910.66, OSHA 1926.502(d), ANSI A10.32, and ANSI Z359.1 requirements
- Accommodates working thicknesses up to 4" (101.6mm)
- Includes: 5/8" Grade 8 bolt, Lockwasher, Nut
- Type: Permanent
- Style: D-Ring
- Max. Working Load: 400 lbs. (181kg)
- Tensile Strength: 5000 lbs. (22kN)
- Material: Drop Forge Alloy Steel
- Weight: 1 lb. 8 oz. (0.7kg)

**Honeywell**  
**MILLER**

Model No.	Mfg. No.	Price /Each
SEP264	416/	



## ANCHORAGE CONNECTOR

- Reusable chain with 'O' Ring for steep-pitched or flat roof
- Type: Temporary
- Style: Roof



Model No.	Mfg. No.	Price /Each
SHB921	RA30-1/	

## ROOF ANCHORS

- Ideal for new construction or as a retrofit on roofs with asphalt, shake or tile roofing materials
- Multiple use applications: new roof/shingle installation, gutter cleaning, window and skylight cleaning/repair, chimney maintenance and general roof maintenance
- Stainless steel body construction and zinc-plated steel D-rings resist corrosion for long service life
- Designed to provide two (2) D-ring anchorage points when securely installed on a wood roof sub-surface
- Accommodates single user of up to 310 lbs. (140.6kg) for fall protection
- Meets OSHA 1926.502 guideline
- Type: Permanent
- Style: D-Ring
- Material: Stainless Steel

**Honeywell**  
**MILLER**

Model No.	Mfg. No.	Description	Price /Each
SEP482	RA40/	Double Roof Anchor	
SEP483	RA41/	Single Roof Anchor	



## D-BOLT PERMANENT ANCHORAGE CONNECTORS

- 1/2" diameter D-bolt anchor
- One-piece unit with lockwasher and nut
- 400-lb. maximum capacity

**Honeywell**  
**MILLER**

Model No.	Mfg. No.	Price /Each
SD005	415	



## ANCHORAGE CONNECTOR

- D-bolt anchor without hardware
- Can be installed on a vertical wall or overhead for versatility
- Type: Permanent
- Style: D-Ring

**Honeywell**  
**MILLER**

Model No.	Mfg. No.	Price /Each
SHB920	417/	



## BEAM TROLLEYS

- Steel anchor point that can be attached to horizontal I-beams
- Adjustable beam trolley slides along with the worker to provide maximum mobility
- 400-lb. maximum capacity

**Honeywell**  
**MILLER**

Model No.	Mfg. No.	Description	Beam Width"	Price /Each
SD010	9065/BK	Beam Trolley	3 to 4 1/2	
SAK435	9065-1	Adapter Kit for SD010	3 to 8 1/2	



## SWIVEL ANCHOR

- Provides freedom of movement with innovative swivel design that offers 360° D-ring rotation and 180° flip
- For use in concrete
- 10 000 lbs. (10K) tensile strength
- Rated for up to a 310 lbs (141 kg) user
- Type: Permanent
- Style: D-Ring

**Honeywell**  
**MILLER**

Model No.	Mfg. No.	Price /Each
SHB923	RACSWY100C	



## CLAW ANCHORAGE ROOF CONNECTOR

- Designed to provide a single anchorage point when securely installed on a wood rafter or truss member
- Fits wood sizes 2" x 4", 2" x 6", 2" x 8", 2" x 10" or 2" x 12"
- Stainless steel construction
- Accommodates single user for fall protection
- Type: Permanent



**Honeywell**  
**MILLER**

Model No.	Mfg. No.	Price /Each
SHB922	RA45/	